

SLP160S-12

High Efficiency Monocrystalline PV Module




Electrical Characteristics	SLP160S-12
Product code	160021203
Maximum power (Pmax)	160W
Voltage at Pmax (Vmp)	18.2V
Current at Pmax (Imp)	8.80A
Open-circuit voltage (Voc)	21.9V
Short-circuit current (Isc)	9.60A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/ °C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

*NOCT: Nominal operating cell temperature (the data is only for reference)


Module Diagram



Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



SLP160S-12 I-V Curves

Specifications	SLP160S-12
Cells	Monocrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	1500mm[59.06in.].x675mm[26.57in.].x35mm[1.38in.]
Weight	12.0kg[26.46lbs]
Packing information(Carton)	1545mm[60.83in.].x720mm[28.35in.].x70mm[2.76in.]/(1pc/ctn)

*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

*Specifications are subject to change without notice at any time.